



DALI loudspeakers

The Evidence series	Evidence 870
Frequency range+/- 3 dB [Hz] min	35
Frequency range+/- 3 dB [Hz] max	29000
Sensitivity (2,83 V/1 m) [dB]	91
Nominal impedance [ohms]	4
Maximum SPL [dB]	113
Recommended amp. power [Watts] min	30
Recommended amp. power [Watts] max	500
Crossover frequencies [Hz]	600/3.000
High frequency driver, Quantity	1
High frequency driver, Dimension	1"
High frequency driver, Diaphragm type	Soft textile dome
Midrange driver, Quantity	1
Midrange driver, Dimension	5"
Midrange driver, Diaphragm / cone type	Paper fiber cone
Low frequency driver, Quantity	2
Low frequency driver, Dimension	8"
Low frequency driver, Diaphragm / cone type	Paper fiber cone
Enclosure type	Bass reflex
Bass reflex tuning frequency [Hz] (for bass reflex systems)	31
Connection input(s)	Bi-wire
Recommended placement(s)	Floor
Recommended distance from wall [cm]	10 - 100
Dimensions (H) [cm]	105
Dimensions (W) [cm]	24
Dimensions (D) [cm]	37
Dimensions (H) [inches]	41,2
Dimensions (W) [inches]	9,6
Dimensions (D) [inches]	14,5
Weight [kg]	29
Weight [lb]	63,8
Finish (type)	Veneer
Available Colour(s)	Cherry/Maple/Black Ash